



CHANGE: HOLDING TRACK KFT; EDITORIAL

**STANDARD DEPARTURE ROUTES - INSTRUMENT
SID's**

**KLAGENFURT
RWY 10L**

Calculation of the SID's is based on an all - engines operative minimum net climb gradient of 3.3% (205 FT/NM). MAX IAS during initial turn 205 KT, bank angle at least 20° - thereafter MAX IAS 250 KT up to 10000 FT MSL. Where a greater climb gradient for a specific SID (or part of SID) is necessary this is indicated in the description of the route. For obstacles in the vicinity of the aerodrome see Aerodrome Obstacle Chart Type B. If radar vectoring is provided the climb gradient of the cleared SID shall be continued.

Due to mountainous terrain in the vicinity of Klagenfurt and as well as along the departure flight path and the unusual high climb gradient it is absolutely necessary that pilots observe the required minimum climb gradient as indicated for each departure route.

Aircraft unable to comply with the prescribed climb gradient shall use departure route KFT.

Contingency procedures are under the responsibility of the operator.

For noise abatement reasons departing ACFT should use RWY 10L whenever possible!

To expedite traffic, ATC may request aircraft to start the initial turn with visual reference to terrain when passing 3000 FT MSL. In this case terrain clearance has to be assured by the pilot until passing 6500 FT MSL.

Designator	Route	After Take-Off		Remarks						
		Climb to ..initially	Expect FREQ							
ABIRI 1 L Abiri one lima departure	Climb on track 103° to VOR/DME KFT - ABIRI	By ATC	KLAGENFURT RADAR 123.325	Climb gradient at least 5,5% (335 FT/NM).						
Contact KLAGENFURT RADAR when advised by Tower										
RNAV SID Coding Table of ABIRI 1 L										
Path Terminator	Waypoint			Course/ Track ° MAG (° True)	DIST NM	Turn Direction	Constraints		Navigation Specification	Remarks
	Identifier	Flyover	Coordinates				Level	Speed		
CF	VOR/DME KFT	yes	N463551.30 E0143344.35	103° (106.0°)				K205-	RNAV 1	
DF	ABIRI	no	N464545.01 E0145803.26			left	A9000+		RNAV 1	

Designator	Route	After Take-Off		Remarks						
		Climb to ..initially	Expect FREQ							
BERTA 1 L Berta one lima departure	Climb on track 103° to VOR/DME KFT - BERTA	By ATC	KLAGENFURT RADAR 123.325	Climb gradient at least 8.5% (520 FT/NM).						
Contact KLAGENFURT RADAR when advised by Tower										
RNAV SID Coding Table of BERTA 1 L										
Path Terminator	Waypoint			Course/ Track ° MAG (° True)	DIST NM	Turn Direction	Constraints		Navigation Specification	Remarks
	Identifier	Flyover	Coordinates				Level	Speed		
CF	VOR/DME KFT	yes	N463551.30 E0143344.35	103° (106.0°)				K205-	RNAV 1	
DF	BERTA	no	N462658.95 E0143730.85			right	A11000+		RNAV 1	

**STANDARD DEPARTURE ROUTES - INSTRUMENT
SID's**

**KLAGENFURT
RWY 10L**

Calculation of the SID's is based on an all - engines operative minimum net climb gradient of 3.3% (205 FT/NM). MAX IAS during initial turn 205 KT, bank angle at least 20° - thereafter MAX IAS 250 KT up to 10000 FT MSL. Where a greater climb gradient for a specific SID (or part of SID) is necessary this is indicated in the description of the route. For obstacles in the vicinity of the aerodrome see Aerodrome Obstacle Chart Type B. If radar vectoring is provided the climb gradient of the cleared SID shall be continued.

Due to mountainous terrain in the vicinity of Klagenfurt and as well as along the departure flight path and the unusual high climb gradient it is absolutely necessary that pilots observe the required minimum climb gradient as indicated for each departure route.

Aircraft unable to comply with the prescribed climb gradient shall use departure route KFT.

Contingency procedures are under the responsibility of the operator.

For noise abatement reasons departing ACFT should use RWY 10L whenever possible!

To expedite traffic, ATC may request aircraft to start the initial turn with visual reference to terrain when passing 3000 FT MSL. In this case terrain clearance has to be assured by the pilot until passing 6500 FT MSL.

Designator	Route	After Take-Off		Remarks
		Climb to ..initially	Expect FREQ	
INGID 2 L Ingid two lima departure	Climb on track 103° to WK610 - WK611 - INGID	By ATC	KLAGENFURT RADAR 123.325	Climb gradient at least 6,5% (395 FT/NM) until passing 10000 FT MSL, thereafter 3.3% (205 FT/NM).

Contact KLAGENFURT RADAR when advised by Tower

RNAV SID Coding Table of INGID 2 L

Path Terminator	Waypoint			Course/ Track ° MAG (° True)	DIST NM	Turn Direction	Constraints		Navigation Specification	Remarks
	Identifier	Flyover	Coordinates				Level	Speed		
CF	WK610	yes	N463715.91 E0142637.61	103° (106.3°)				K205-	RNAV 1	
DF	WK611	no	N464945.76 E0141659.49			left	A10000+		RNAV 1	
TF	INGID	no	N471606.73 E0134106.67	314° (317.3°)	36.0		A11500+		RNAV 1	

Designator	Route	After Take-Off		Remarks
		Climb to ..initially	Expect FREQ	
KFT 1 L Klagenfurt one lima departure	Climb on track 103 until passing VOR/DME KFT, turn LEFT and follow R-056 KFT up to 6000 FT MSL, turn LEFT inbound to VOR/DME KFT and enter to the holding	By ATC	KLAGENFURT RADAR 123.325	Only available for 1. NON-RNAV equipped aircraft, 2. IFR training flights. Initial turn MAX IAS 205 KT. Climb gradient up to 8500 FT MSL at least 4% (245 FT/NM). Pass VOR/DME KFT at or above 3700 FT MSL. Do NOT enter the holding below 8500 FT MSL!

Contact KLAGENFURT RADAR when advised by Tower

Designator	Route	After Take-Off		Remarks
		Climb to ..initially	Expect FREQ	
KLAGY 1 L Klagy one lima departure	Climb on track 103° to VOR/DME KFT - KLAGY	By ATC	KLAGENFURT RADAR 123.325	Climb gradient at least 7,4% (450 FT/NM).

Contact KLAGENFURT RADAR when advised by Tower

RNAV SID Coding Table of KLAGY 1 L

Path Terminator	Waypoint			Course/ Track ° MAG (° True)	DIST NM	Turn Direction	Constraints		Navigation Specification	Remarks
	Identifier	Flyover	Coordinates				Level	Speed		
CF	VOR/DME KFT	yes	N463551.30 E0143344.35	103° (106.0°)				K205-	RNAV 1	
DF	KLAGY	no	N463051.48 E0144630.61			right	A10000+		RNAV 1	

**STANDARD DEPARTURE ROUTES - INSTRUMENT
SID's**

**KLAGENFURT
RWY 10L**

Calculation of the SID's is based on an all - engines operative minimum net climb gradient of 3.3% (205 FT/NM). MAX IAS during initial turn 205 KT, bank angle at least 20° - thereafter MAX IAS 250 KT up to 10000 FT MSL. Where a greater climb gradient for a specific SID (or part of SID) is necessary this is indicated in the description of the route. For obstacles in the vicinity of the aerodrome see Aerodrome Obstacle Chart Type B. If radar vectoring is provided the climb gradient of the cleared SID shall be continued.

Due to mountainous terrain in the vicinity of Klagenfurt and as well as along the departure flight path and the unusual high climb gradient it is absolutely necessary that pilots observe the required minimum climb gradient as indicated for each departure route.

Aircraft unable to comply with the prescribed climb gradient shall use departure route KFT.

Contingency procedures are under the responsibility of the operator.

For noise abatement reasons departing ACFT should use RWY 10L whenever possible!

To expedite traffic, ATC may request aircraft to start the initial turn with visual reference to terrain when passing 3000 FT MSL. In this case terrain clearance has to be assured by the pilot until passing 6500 FT MSL.

Designator	Route	After Take-Off		Remarks
		Climb to ..initially	Expect FREQ	
REKTI 1 L Rekti one lima departure	Climb on track 103° to WK610 - WK612 - REKTI	By ATC	KLAGENFURT RADAR 123.325	Climb gradient at least 6.5% (395 FT/NM) until passing 3000 FT MSL, thereafter 5,0% (305 FT/NM).

Contact KLAGENFURT RADAR when advised by Tower

RNAV SID Coding Table of REKTI 1 L

Path Terminator	Waypoint			Course/ Track ° MAG (° True)	DIST NM	Turn Direction	Constraints		Navigation Specification	Remarks
	Identifier	Flyover	Coordinates				Level	Speed		
CF	WK610	yes	N463715.91 E0142637.61	103° (106.3°)				K205-	RNAV 1	
DF	WK612	yes	N464002.91 E0141305.71			left	A8000+		RNAV 1	
DF	REKTI	no	N463504.34 E0135350.81			left	A11000+		RNAV 1	

Designator	Route	After Take-Off		Remarks
		Climb to ..initially	Expect FREQ	
VILAK 1 L Vilak one lima departure	Climb on track 103° to WK610 - WK612 - VILAK	By ATC	KLAGENFURT RADAR 123.325	Climb gradient at least 6.5% (395 FT/NM) until passing 3000 FT MSL, thereafter 5,0% (305 FT/NM).

Contact KLAGENFURT RADAR when advised by Tower

RNAV SID Coding Table of VILAK 1 L

Path Terminator	Waypoint			Course/ Track ° MAG (° True)	DIST NM	Turn Direction	Constraints		Navigation Specification	Remarks
	Identifier	Flyover	Coordinates				Level	Speed		
CF	WK610	yes	N463715.91 E0142637.61	103° (106.3°)				K205-	RNAV 1	
DF	WK612	yes	N464002.91 E0141305.71			left	A8000+		RNAV 1	
DF	VILAK	no	N464147.01 E0135452.72				A10000+		RNAV 1	

RNAV Holding

Holding Point	Inbound Track ° True	Inbound Track ° MAG	Turn Direction	MAX IAS	Minimum Holding Altitude FT MSL / FL	Time	DIST NM	Remarks
VILAK	139.4°	136°	right		A10000	1 MIN		