


**INSTRUMENT
APPROACH
CHART - ICAO**

VAR 5° E


AD ELEV 600 FT
THR 29 ELEV 600 FT
HGT RELATED TO THR ELEV

RADAR	118.775	125.175	129.050	134.675	136.250
ARRIVAL	119.800	134.125			
TOWER	119.400	123.800	124.475		
GROUND	121.600	121.775			
ATIS	122.955				

WIEN-SCHWECHAT (LOWW)
ÖSTERREICH AUSTRIA
ILS Z CAT II & III or LOC Z RWY 29



CHANGE: EDITORIAL



MISSED APPROACH: CLIMB STRAIGHT AHEAD, AT D-10.0 OEX TURN RIGHT DIRECT TO FMD;
CLIMB TO 5000 FT AMSL AND HOLD.

OCA (OCH) IN FT	A	B	C	D / D _L
CAT I Press. Altim.	749 (149)	761 (161)	773 (173)	783 (183)
CAT II RDO Altim.	661 (61)	678 (78)	690 (90)	708 (108)
CAT III	A P P R O V E D			
LOC-DME	1220 (620)			

D-7.5 OEX to THR 29 - DISTANCE 7.4 NM (Timing not authorized for defining the MAPt)							
	GS (KT)	80	100	120	140	160	180
Rate of descent (5.2%)	FT / MIN	420	530	640	740	850	960

DME OEX	7	6	5	4	3	2
DIST THR	6.9	5.9	4.9	3.9	2.9	1.9
ALT (HEIGHT)	2840 (2240)	2520 (1920)	2200 (1600)	1880 (1280)	1560 (960)	1240 (640)